

CPU/CONTESSA MADEIRA

Product Specifications

Pointe.
International

Application

Upholstery

Content

100% CPU - Clean Performance Urethane

Backing

65% Polyester / 35% Cotton

Width

54"

Repeat

N/A

General Characteristics

Abrasion : 200,000+ double rubs (Wyzenbeek)†

Hydrolysis Resistance : 15+ weeks

- ISO1419:1995, Method C, Tropical Test

Colorfastness to light (AATCC-16/200 hours)

Meets or Exceeds all ACT Heavy Duty Performance
Guidelines for Upholstery

Flammability

CA Bulletin 117-2013, UFAC/NFPA 260-Class 1

IMO A652 (16) 8.2

Environmental

Solvent/DMF Free, PVC/Phthalates Free, FR/Anti-
Microbial Free

*Complies with REACH, Prop 65, HHI, CAL 01350

Maintenance

W/S, Bleach Cleanable (10:1)

Warranty


Please refer to our Terms of Sales for warranty
information.



Sumatra



Fossil



Alloy



Clay




Trail



Thrill



Storm



Quarry



Harbor



Graphite

† Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be a reliable indicator of increased fabric lifespan.